




NEW

# AQUASTORM

DESCRIPTION: Paver TEXTURE: Smooth

## PALLET OVERVIEW



Specifications per pallet		Imperial	Metric
Cubing		78.39 ft <sup>2</sup>	7.28 m <sup>2</sup>
Weight		2412 lbs	1 094 kg
Number of rows		7	
Coverage per row		11.20 ft <sup>2</sup>	1.04 m <sup>2</sup>
Linear coverage per row	Depth	13.39 lin. ft	4.08 lin. m
	Length	6.69 lin. ft	2.04 lin. m



Aqua Storm paver meet and exceeds the requirements of ASTM C1319 for Concrete Grid Paving Units.


## NOTES

Aquastorm is only available in Eastern USA. See page 15 for list of Eastern States.


See page 44 to 47 for more technical information. When used in a permeable pavement application, see page 83 to 89 for more technical information.

**JOINT WIDTH: 1 5/8" ( 41 mm)**  
**% OF SURFACE OPENING: 38 %**


Unit dimensions	in		mm		Units /pallet
	in	mm	in	mm	
Height	3 15/16	100			56 units
Depth	10 1/16	255			
Length	20 1/16	510			




01 | Herringbone pattern



02 | Linear pattern



03 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

grey

